



MB2100

File Number: E80533Yellow Card® **COMPANY****Mar-Bal Inc**787 Renaissance Parkway
Painesville, OH 44077 United States**MODEL INFO****MB2100**

Unsaturated Polyester (UP), glass reinforced, furnished as bulk

FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability		ANSI/UL 94
3.0 mm, Color: ALL	V-0	
4.0 mm, Color: ALL	V-0	
ISO/IEC FLAMMABILITY PROPERTIES	VALUE	TEST METHOD
Flammability		IEC 60695-11-10
3.0 mm, Color: ALL	V-0	
4.0 mm, Color: ALL	V-0	
ELECTRICAL PROPERTIES	VALUE	TEST METHOD
Hot-wire Ignition (HWI)		UL 746A
3.0 mm	PLC 0	
4.0 mm	PLC 0	
High Amp Arc Ignition (HAI)		UL 746A

3.0 mm	PLC 0	
4.0 mm	PLC 0	
Comparative Tracking Index (CTI)	PLC 0	UL 746A
Dielectric Strength	24 kV/mm	ASTM D149
THERMAL PROPERTIES	VALUE	TEST METHOD
Relative Thermal Index - Electrical Strength		UL 746B
3.0 mm	130 °C	
4.0 mm	130 °C	
Relative Thermal Index - Mechanical Impact		UL 746B
3.0 mm	130 °C	
4.0 mm	130 °C	
Relative Thermal Index - Mechanical Strength		UL 746B
3.0 mm	130 °C	
4.0 mm	130 °C	

Report Date: 2020-10-23
Revision Date: 2020-11-04

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"